

**AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions and listings of claims in the application.

**Listing of claims**

1. (previously presented) An adjuster and bracket assembly comprising:  
  
a mounting bracket having a rear surface configured to stationarily mount to a vehicle, a front surface and side edges therebetween, the mounting bracket having stationary arms extending frontwardly from one of the front surface and the side edges of the mounting bracket, the stationary arms dimensioned to pivotally receive a reflector; and,  
  
an adjuster secured to the rear surface of the mounting bracket such that when the reflector is pivotally received by the stationary arms of the mounting bracket after the adjuster has been secured thereto, the adjuster communicates with the reflector such that rotation of an aiming screw within the adjuster causes pivoting of the reflector within the stationary arms of the mounting bracket.
2. (previously presented) The adjuster and bracket assembly of claim 1 wherein the reflector is snap-fitted onto at least one of the stationary arms of the mounting bracket.
3. (original) The adjuster and bracket assembly of claim 1 wherein the mounting bracket has a head retaining bracket, the aiming screw of the adjuster fitted into the head retaining bracket.
4. (previously amended) An adjuster and bracket assembly comprising:

a mounting bracket, having stationary arms extending forwardly therefrom, the stationary arms dimensioned to pivotally receive a reflector; and,

an adjuster secured to the mounting bracket such that when the reflector is pivotally received by the stationary arms of the mounting bracket after the adjuster has been secured thereto, the adjuster communicates with the reflector such that rotation of an aiming screw within the adjuster causes pivoting of the reflector within the stationary arms of the mounting bracket, wherein the aiming screw has a screw boss threaded thereon, the screw boss in communication with the reflector when the reflector is pivotally received by the mounting bracket such that rotation of the aiming screw causes the screw boss to move along the aiming screw resulting in a pivoting of the reflector.

5. (original) The adjuster and bracket assembly of claim 4 wherein the screw boss mates with a fin extending from the reflector when the reflector is pivotally received by the mounting bracket.
6. (original) The adjuster and bracket assembly of claim 5 wherein the screw boss has a tab that engages a slot in the fin when the reflector is pivotally received by the mounting bracket.
7. (original) The adjuster and bracket assembly of claim 5 wherein the screw boss has at least one engagement channel that engages a slot in the fin when the reflector is pivotally received by the mounting bracket.
8. (original) The adjuster and bracket assembly of claim 4 wherein the screw boss is slidably engaged to the mounting bracket.

9. (original) The adjuster and bracket assembly of claim 8 wherein the screw boss is in sliding engagement with a rail on the mounting bracket such that rotation of the aiming screw causes the screw boss to slide along the rail resulting in pivoting of the reflector.
10. (original) The adjuster and bracket assembly of claim 9 wherein the rail is substantially parallel to the aiming screw.
11. (canceled)
12. (previously presented) The adjuster and bracket assembly of claim 1 wherein the reflector has a plurality of posts, and wherein each of the stationary arms of the mounting bracket functionally engage one of the posts such that actuation of the adjuster causes the reflector to pivot on the posts.
13. (previously presented) A lamp assembly comprising:
  - a lamp having a lens, a reflector and a bulb;
  - a mounting bracket having a rear surface configured to be stationarily secured to a vehicle and a front surface, having stationary arms extending frontwardly therefrom, the stationary arms dimensioned to pivotally receive the reflector; and,
  - an adjuster secured to the rear surface of the mounting bracket such that the reflector is pivotally receivable by the stationary arms of the mounting bracket after the adjuster has been secured to the mounting bracket, the adjuster communicates with the reflector when the reflector is received by the mounting bracket such that rotation of an aiming screw within the adjuster causes pivoting of the reflector within the stationary arms of the mounting bracket.

14. (original) The lamp assembly of claim 13 further comprising a screw boss threaded onto the aiming screw and slidingly engaged to the mounting bracket.
15. (previously presented) A lamp assembly comprising:
- a lamp having a lens, a reflector and a bulb;
  - a mounting bracket, having stationary arms extending forwardly therefrom, the stationary arms dimensioned to pivotally receive the reflector; and,
  - an adjuster secured to the mounting bracket such that the reflector is pivotally receivable by the stationary arms of the mounting bracket after the adjuster has been secured to the mounting bracket, the adjuster communicates with the reflector when the reflector is received by the mounting bracket such that rotation of an aiming screw within the adjuster causes pivoting of the reflector within the stationary arms of the mounting bracket; and
  - a screw boss threaded onto the aiming screw and slidingly engaged to the mounting bracket, wherein the screw boss slides along a guide rail extending from the mounting bracket.
16. (original) The lamp assembly of claim 15 where the guide rail is substantially parallel to the aiming screw.
17. (original) The lamp assembly of claim 13 where the reflector snap fits into the mounting bracket.
18. (canceled)
19. (canceled)
20. (canceled)
21. (canceled)

22. (previously presented) A lamp assembly comprising:

a mounting bracket having a rail; and,

an adjuster secured to the mounting bracket such that the adjuster and mounting bracket form a unit having stationary arms extending forwardly therefrom which pivotally receive a reflector, where the adjuster has:

an aiming screw journaled by the mounting bracket; and,

a screw boss functionally engaged to the aiming screw, slidely engaged to the rail, and functionally engaged to the reflector such that rotation of the aiming screw causes the screw boss to move along the axis of the aiming screw and slide along the rail thereby pivoting the reflector within the stationary arms of the unit.

23. (original) The lamp assembly of claim 22 wherein the rail and the aiming screw are substantially parallel to one another.

24. (original) The lamp assembly of claim 22 wherein the reflector snap fits into the unit.

25. (canceled)

26. (canceled)

27. (canceled)

28. (canceled)

29. (canceled)

30. (canceled)

31. (canceled)